



# EverPro GLOVES

Coated Work Gloves Manufacture Since 2011

15 Gauge HPPE Liner With  
Nitrile Sandy Thumb Coated Cut  
Resistant Work Glove (Cut 701)

## SPECIFICATION

### PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide the glove cut level to 5, suitable to most of the high cut risk conditions. Nitrile sandy coating can be oil-resistant and water-resistant. and workable both in wet and dry conditions. Thumb coated supply more protection to hands. For cut resistant glove the abrasion and tear performance all can arrive level 4.

### APPLICATIONS

- √ Construction
- √ Furniture manufacturing
- √ Glass Process
- √ Automobile subassembly
- √ Car and ship Manufacture
- √ Intricate assembly
- √ Light sheet metal assembly




### FEATURES

- Color: Blue/black
- Liner Material: Cut 5 HPPE
- Coating Material: Nitrile
- Finishing: Sandy palm and thumb
- Package: 12pairs/bag, 120pairs/carton
- Printing: ink/silk/heat transfer

### ADVANTAGES

- √ Cut level 5
- √ High flexible performance
- √ Thinner and soft feeling
- √ Keep good grip both the wet and dry work conditions
- √ Good function of oil-resistant and water-resistant

### EN388 MECHANICAL RISKS



Charater	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance(number of cycles)	100	500	2000	8000	-
Blade cut resistance(index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture reistance	20	60	100	150	-
Cut resistance method (EN ISO 13997 )	A to F				